

# ODAC® 63TRIO

## Diameter Scanner and Flaw Detector in One Unit

ZUMBACH, pioneer of on-line measurement and its triple-axis ODAC TRIO laser diameter gauges belong to the market leaders of super fast diameter measuring devices. 3 synchronized measurement axis in 1 single plane provide comprehensive measurement coverage, peak-precision diameter and ovality measurement as well as precise and super-fast flaw detection capabilities. Such combinations will help to reduce system costs due to the combination of diameter measurement and flaw detection into one single measuring device. Thanks to the compact design, the ODAC® 63TRIO measuring heads can be used in virtually every manufacturing process in the wire and cable industry, the plastics and rubber industry as well as the steel and metal industry. Known for precision, quality and ease of use the laser measuring heads from ZUMBACH are among the best of their class. The technological basis considered for these measuring heads is always of the latest cutting edge technology, with laser diodes as light sources combined with intelligent and powerful measured-value processors which facilitate a simple and flexible integration. Our long-standing experience as a pioneer of in-line measuring technology, combined with high production figures result in a product with an excellent price-performance ratio.

Amongst the outstanding features are features such as single scan calibration (CSS), single scan monitoring and high data rate output of up to 200\* data packages per second.

The measuring heads can be used with all line speeds. Vibrations during production have no noticeable influence on measurements.

## Adaptive signal processing in the measuring units increase accuracy

All the measuring heads of the ODAC® series have adaptive signal processing (patent DE3111356), which makes subsequent regular re-calibrations superfluous. Only in instances of component exchange or compliance to calibration regulations ISO 9001 etc. would re-calibration be required. All the relevant parameters for accuracy are continuously monitored by the measuring system and automatically compensated. This is valid in particular also for possible long-term changes of the behaviour of the scanner motor or the measuring electronics.

\* Depending on the measuring head model, the number of transmitted measured values as well as the baud rate of the interface.



## Main Advantages

- 9000 measurements per second (FF version)
- 3 synchronized measurement axes on 1 single plane
- Single scan monitoring – up to 9000 scans/second
- Reliable detection of the ovality
- Detects any deviation from roundness of oval and out-of-round with polygonal shape (multi-lobe)
- Yields highly accurate mean value, regardless of the orientation of the product ovality
- Computes accurate values of circumference and cross section (important for fittings of tubes and hoses)
- Increased measurement accuracy and reliability
- High dirt and dust tolerance




Display unit (option):  
 VISU-Touch or LOC 01

## Comparison of 3- and 2-axis measurement: Orientation of the object



# System Overviews


## ODAC® 63TRIO-EN-RS (serial interface)



The built-in processor allows the acquisition and monitoring of the measured values, as well as statistic functions, parameter selection and many other functions. The RS version communicates via the integrated RS interface with a higher level system, like USYS from Zumbach, Host

computer (or PLC). The Zumbach protocols ODAC or Host are selectable according to choice. The service interface (Ethernet TCP/IP) is used for configuring the measuring system.


## ODAC® 63TRIO-EN-DP (Profibus DP), -EN-PN (Profinet IO) or -EN-EI (EtherNet/IP)



The built-in processor allows the acquisition and monitoring of the measured values, as well as statistic functions, parameter selection and many other functions. These versions communicate via the integrated Profibus DP, Profinet IO or EtherNet/IP interface with a higher level system. These interfaces are designed for high speed data transfer at

the sensor actuator level. At this level, controllers such as programmable logic controllers (or PLC's) exchange data via a fast serial (Profibus DP) or Ethernet (Profinet IO) connection with their distributed peripherals such as drivers, valves or intelligent slaves like ODAC measuring heads from Zumbach.

## ODAC® 63TRIO-EN-EN (Ethernet)



The built-in processor allows the acquisition and monitoring of the measured values, as well as statistic functions, parameter selection and many other functions. The EN version communicates via the integrated EN interface with a higher level system. The measured values and

parameters are integrated and transferred using a selectable Zumbach protocol (ODAC or Host protocol) in standardized packages of the TCP/IP. TCP/IP allows the data transfer through existing networks such as LANs and others.

## ODAC® 63TRIO-J with the corresponding external ZUMBACH processors



# Accessories

## Description


## Order Number

### Floor stand ST2-ODAC 63TRIO

ST02.103.75750

Vertically adjustable.

Line height (H): 900...1200 mm (35.43...47.25 in.)



### Swivel floor stand ST2-ODAC 63TRIO

ST06.150.63000

Vertically adjustable.

Line height (H): 860...1150 mm (33.86...45.28 in.)  
Swivel angle: 90° (upward)



### Mountable support for ST2

ST02.060.190

Lateral support, including rotary holder (USY.0002.910) for table top version of the USYS 20 processor.



### Limiting socket VF63-ODAC63

ODAC.631.420

The ceramic limiting socket is only a device to delimit the measuring field. It has no guiding function.



### Set of calibration standards

ODAC.9500.89000

Delivered in a protection box, comprising:

- Calibration standard holder
- Calibration standard  $\varnothing$  2 and 50 mm
- Certificate, other calibration standards on request.



### Local display LOC 01

LOC.011.01000

Is mounted directly on the measuring head. Requires connection cable # ODAC.9167.00004 between LOC 01 and the measuring head. Not for ODAC J versions.



### VISU-Touch

VISU.001.01XXX

The VISU-Touch is a rugged and compact 7" touch screen. This universal PoE (Power over Ethernet) powered touch screen enables display of the integrated web interface of the connected measuring head. It is supplied with a holder for fixing on the measuring head. Not for ODAC J versions.



### Ethernet cable

A15 608 8XXX

Ethernet network cable cat. 6 S/FTP with RJ45 connectors. (XXX in the order number stands for: x 0.1 m, e.g. A15 608 8025 stands for 25 x 0.1 m and thus a cable that is 2.5 m long). Not for ODAC J versions.

### PoE Injector 48V, 24W

N2.7860.1000

Power over Ethernet supply for devices that do not support PoE or a long Ethernet cable. Not for ODAC J versions.



### Analogue interface AI4-R

ODAC.001.100

Interface with 4 analogue, 5 digital and 2 relay outputs. Direct connection of the digital input (proximity switch). Not for ODAC J versions.



### Signal cable L2 Bus 1DR22 x 02R

A13 252 0150

For the connection between the Profibus DP interface and the customer's data acquisition system. Only for DP version.

### Connector

A10 125 0070

Counter connector for digital input "I/F". Connection of a proximity switch. It is not required, if the analogue interface is already used. Not for ODAC J versions.




### Proximity switch

A16 100 0110

The proximity switch is used for the length detection.



Main data:

- Standard: EN 60947-5-6 (NAMUR, NC)
- Switching distance max. 2 mm (.08 in.), flush mounting
- Ambient temperature: -25...100°C (-13...212°F)
- Protection: IP 67, Connection: PVC cable 2 m (6.5 ft.)



# Dimensions

RS/DP/EN/PN/EI: ~74 [2.91]



Dimensions in mm (inch)

# Technical Data

Model	ODAC 63TRIO-	EN-RS	EN-DP	EN-EN	EN-PN	EN-EI	J
<b>Measurement</b>							
Measuring field M <sup>1)</sup>	64 x 64 x 64 mm (2.52 x 2.52 x 2.52 in.)						
Min. object $\phi$	0.25 mm (.01 in.) (standard and F version); FF version: 0.5 mm (.02 in.)						
Scanning frequency	3 x 600 scans/s (standard); F version: 3 x 1500 scans/s; FF version: 3 x 3000 scans/s						
Scanning speed	173 m/s (567.6 ft./s) (standard); F version: 432.5 m/s (1419 ft./s); FF version: 865 m/s (2837.9 ft./s)						
Width of laser beam <sup>3) 5)</sup>	3.5 mm (.14 in.) (standard); xN (Narrow Beam version) 0.5 mm (.02 in.)						
Repeatability (3 $\sigma$ )	0.8 $\mu$ m (.000032 in.) (standard and F version); 0.3 $\mu$ m (.000012 in.) (standard and F version);		FF version: 1.10 $\mu$ m (.000043 in.) FF version: 0.45 $\mu$ m (.000018 in.)		(averaging time 0.1 s) (averaging time 1 s)		
Measurement error	$\pm 2 \mu$ m (.00008 in.) $\pm 0.1 \%$						
Resolution <sup>2)</sup>	0.1 $\mu$ m (.000005 in.)						
Light source <sup>4)</sup>	VLD (Visible Laser Diode) 630-680 nm, laser class 2 (device)						
<b>Interfaces / Connections</b>							
Interface Service	Ethernet TCP/IP, RJ45 10/100BaseT, galvanically isolated						Only J interfaces to Zumbach processors: USYS 20, USYS 200, USYS IPC 1e, USYS IPC 2e, CI 1J/EN-RS/-DP/-EN/-PN/-EI
Interface Host	RS-232/-422/-485, D-sub. connectors 9p./m, galvanically isolated	Profibus DP (RS-485), D-sub. connector 9p./f, galvanically isolated	Ethernet TCP/IP, 2 x RJ45 10/100BaseT, galvanically isolated	Profinet IO, 2 x RJ45 10/100BaseT, galvanically isolated	EtherNet/IP, 2 x RJ45 10/100BaseT, galvanic. isolated		
Data rate max. standard	200/s	50/s	200/s	50/s	200/s		
Data rate max. F version	188/s	125/s	188/s	125/s	150/s		
Data rate max. FF version	125/s	125/s	125/s	125/s	100/s		
Interface LOC	Only for Zumbach local display LOC 01						
Interface I/F	Can be used for the connection of a remote interface (e.g. AI4-R) or as digital input for length detector (e.g. proximity switch according to EN 60947-5-6, NAMUR)						
Indicator of contamin. windows	Flashing LED on the measuring head						
LED Service interface	Indicates link and traffic						-
LED Host interface	Indicates traffic	Indicates traffic and error	Indicates link and traffic	Indicates link, traffic, system error and bus error	Indicates link, traffic, module status and network status	-	
<b>Energy supply</b>							
Mains voltage	100-240 VAC						Supplied by the processor unit (24VDC / 8W)
Operating range	85-265 VAC typically						
Mains frequency	50/60 Hz						
Operating range	47-63 Hz typically						
Power	30 VA						
<b>Operation conditions / Miscellaneous</b>							
Ambient temperature	Operating: 0...45°C (32...113°F), Transport / Storage: -20...50°C (-4...122°F)						
Max. atmospheric humidity	95% (non condensing)						
Altitude	0...3000 m (0...9843 ft.) over sea level						
Type of protection <sup>6)</sup>	Case IP 65, connection plate IP 40						
Weight	9.8kg (21.6 lbs)						

<sup>1)</sup> M stands for measuring field height. In practice, the largest object diameter corresponds to Measuring Field Height minus instability of position.


<sup>2)</sup> System resolution is the smallest practical value on the last digit of the display.

<sup>3)</sup> Measured in the measuring plane, incl. lateral jitter of the scans.

<sup>4)</sup> Maximum power of the laser can be read on the warning label.

<sup>5)</sup> The xxN-F versions (Narrow beam) is recommended in case of products with very uneven surfaces, for the contour measurement and detection of surface defects, such as lumps and neckdowns.

<sup>6)</sup> Conformity not verified by UL.



• Technical specifications are subject to change without notice



## Ordering Information

When ordering, please specify the following:

- 1 **Measuring head models:** ODAC 63TRIO-EN-RS/-DP/-EN/-PN/-EI, ODAC 63TRIO-J
- 2 **Connection cable**
  - 2a The connection between ODAC 63TRIO-EN-RS and the higher level system is to be provided by the customer (via serial interface).
  - 2b For the ODAC 63TRIO-EN-DP versions, the connection to a higher level system is made with the signal cable # A13 252 0150.
  - 2c For the ODAC 63TRIO-EN-EN/-PN/-EI versions, the connection from the measuring head to the customer's Ethernet port, must be provided by the customer.
- 2d **Length** of the connection cable between ODAC 63TRIO-J and the processor.  
Available lengths: 1, 2, 5, 10, 15, 20, 25 and 30 m (3.3, 6.6, 16.4, 32.8, 49.2, 65.6, 82 and 98.5 ft.); Longer cables on request.
- 3 **Processor model** (Data acquisition system), only for ODAC 63TRIO-J: USYS 20, USYS 200, USYS IPC 1e, USYS IPC 2e, CI 1J/EN-RS, CI 1J/EN-DP, CI 1J/EN-EN, CI 1J/EN-PN, CI 1J/EN-EI. Please ask for corresponding data sheets.

## WORLDWIDE CUSTOMER SERVICE AND SALES OFFICES

**Headquarter:**  
Zumbach Electronic AG  
P.O. Box  
CH-2552 Orpund  
SWITZERLAND  
Tel.: +41 (0)32 356 04 00  
sales@zumbach.ch

BENELUX, sales@zumbach.be  
CHINA P.R., sales@zumbach.com.cn  
CZECH REPUBLIC, jvorlicek@zumbach.cz  
FRANCE, ventes@zumbach.com.fr  
GERMANY, verkauf@zumbach.de

INDIA, sales@zumbachindia.com  
ITALY, zumit@zumbach.it  
SPAIN, gestion@zumbach.es  
TAIWAN, info@zumbach.tw  
UK, sales@zumbach.co.uk

**North American Headquarter:**  
Zumbach Electronics Corp.  
140 Kisco Avenue  
Mount Kisco, NY 10549-1407  
Phone +1 914 241 7080  
USA  
sales@zumbach.com

