

RAYEX® S



Static X-Ray Measuring and Control System

EASY AND RELIABLE MEASUREMENT

The new RAYEX S system combines modern X-Ray technology and easy operation in one unit. The high flexibility and convincing performance of RAYEX S are providing significant advantages:


- **Fast installation and commissioning**
- **Easy operation and product setting**
- **Longevity, especially of X-ray sources**
- **Easy maintenance and service**

Easy and Reliable Measurement of Diameter, Ovality, Wall Thickness and Eccentricity for Products up to 100 mm (3.9 in.) Outer Diameter

Cables: Coax, CATV, Silane, Jackets

Tubing/Pipe: PVC, PE, PA, Composite Pipes, Automotive, etc.

Hoses: Rubber, Medical, Silicone, PTFE, etc.



KEY FEATURES AND ADVANTAGES

- **High stability and accuracy**
 - Repeatability within 0.04 mm (.0023 in.)
 - No calibration needed
 - No need for material-specific adjustments
- **Simple concept and easy to use**
 - Display of four wall thickness and two diameter measuring points incl. resulting ovality
 - Two X-ray sources mounted 90° to each other
 - No moving parts
- **X-ray sources**
 - Extremely robust and stable
 - Easy to exchange, no realignment
 - Expected lifetime up to 4 years
 - No water cooling required
- **X-ray safety**
 - Comprehensive shielding concept
 - Minimal scatter, no lead necessary
 - Outside radiation level meets national and international standards
- **For all materials / combinations**
 - Plastics, foam, rubber, composites (metal/plastics), foamed structures
 - Up to four layers measurable
- **Embedded bus communication interface**

The RAYEX S is available with an embedded bus interface for integration into the customer's line control system.

 - User friendly setup of the product recipe
 - Readout of all measurement results possible
 - Ethernet and Profinet IO interfaces available
- **USYS processor and display unit**

The proven Zumbach processors for process monitoring, control and data acquisition.

 - Continuous display of measurement results
 - Recipe management
 - Monitoring of limit values
 - Statistics recording and protocolling
 - Line speed control
 - Compatible with other Zumbach devices

OPTIONS ACCESSORIES

VISU-Touch

The VISU-Touch enables manual control and can be mounted on the RAYEX S or used separately. For applications that are controlled via an interface, the VISU-Touch is used as a local display.

- Graphic display with backlight, signalling, keyboard input
- Power supply from RAYEX S via Ethernet (PoE)
- Ethernet network cable cat. 6 S / FTP with RJ45 connectors

Verification Kit

The set includes a calibration pattern holder and a certified calibration standard for checking.


Blower

To keep the measuring zone free of contamination, we recommend connecting a blower. The unit itself has appropriate connections.




RAYEX S 50/110 SYSTEM OVERVIEWS

Standalone measuring system with USYS RAYEXMASTER



The USYS IPC 1e/2e processors allow complete process control and optimisation. All measured values can be monitored and logged by the software. The stored product recipes enable easy operation of the system. Additional sensors such as: ODAC laser diameter gauges or KW lump detectors can be connected if required. The USYS processors also has inputs and outputs for alarming the line control and can also communicate with a higher-level system via the HOST interface.

Measuring unit with embedded bus communication interface




The design with embedded communication interface allows the higher-level system to configure and capture measurement results. The measuring algorithm itself is controlled by the RAYEX S and only requires the number of layers and the nominal wall thickness to be specified. All measurement results can be read and processed by the higher-level system.

Available interfaces are: Profinet IO, Ethernet TCP/IP, EtherNet IP and OPC UA.

TECHNICAL DATA

System	RAYEX S 50	RAYEX S 110
Product diameter range	4.0 ... ca. 45 mm (.16 ... ca. 1.77 in.)	7.0 ... ca. 100 mm (.275 ... ca. 3.9 in.)
Measuring field	50 mm (1.97 in.)	110 mm (4.3 in.)
Scanning frequency	Standard: 1...10 scans/s	Standard: 1...10 scans/s
Repeatability (σ)	0.04 mm (.0016 in.)	0.06 mm (.0023 in.)
Resolution	5 μ m (.0002 in.)	5 μ m (.0002 in.)
Ambient temperature	Operating: 5...45°C (41...113°F), Transport / storage: 0...50°C (32...120°F)	
Max. atmospheric humidity	95% (non condensing)	
Altitude	0...2000 m (0...6562 ft.) over sea level	
Mains voltage / frequency	230 V version: 210...250 VAC / 50/60 Hz 120 V version: 110...130 VAC / 50/60 Hz	
Power consumption	$P_{nom} = 120 W / P_{max} = 620 W$	
Current consumption	0.5 A _{nom} / 2.6 A _{max} . (230 VAC), 1 A _{nom} / 4.9 A _{max} (120 VAC)	
Fuses	2 fuses in the mains socket: 250 VAC / 5 x 20 mm 6.3 A time-lag	
Weight	RAYEX S 50: approx. 264 kg (582 lbs.), RAYEX S 110: approx. 320 kg (705 lbs.)	
Noise level	≤ 70 dBA	
X-Ray data	55 kV _{max} . / max. 1 mA	
"Service", "Webserver" and "Host" interface	Ethernet 10/100BaseT, RJ45 / IP 20	

DIMENSIONS



Model	RAYEX S 50	RAYEX S 110
A	1040 (40.94 in.)	1240 (48.82 in.)
B	1000 (39.37 in.)	1200 (47.24 in.)
C	680 (26.77 in.)	880 (34.65 in.)

Model	RAYEX S 50	RAYEX S 110
D	808 (31.81 in.)	1058 (41.65 in.)
E	408 (16.06 in.)	458 (18.03 in.)
F	380 (14.96 in.)	430 (16.93 in.)
G	200 (7.87 in.)	300 (11.81 in.)
H	84 (3.31 in.)	134 (5.28 in.)
I	88.9 (3.5 in.)	139 (5.47 in.)

• Technical specifications are subject to change without notice

• Dimensions in mm (inch)

WORLDWIDE CUSTOMER SERVICE AND SALES OFFICES

Headquarter:
Zumbach Electronic AG
P.O. Box
CH-2552 Orpund
SWITZERLAND
Tel.: +41 (0)32 356 04 00
sales@zumbach.ch

BENELUX, sales@zumbach.be
CHINA P.R., sales@zumbach.com.cn
CZECH REPUBLIC, jvorlicek@zumbach.cz
FRANCE, ventes@zumbach.com.fr
GERMANY, verkauf@zumbach.de

INDIA, sales@zumbachindia.com
ITALY, zumit@zumbach.it
SPAIN, gestion@zumbach.es
TAIWAN, info@zumbach.tw
UNITED KINGDOM, sales@zumbach.co.uk

North American Headquarter:
Zumbach Electronics Corp.
140 Kisco Avenue
Mount Kisco, NY 10549-1407
Phone +1 914 241 7080
USA
sales@zumbach.com



RAYX.004.0002.EN APR.2022